

# Material Safety Data Sheet

## 1- Chemical Product and Company Identification:

Product Name: **Fume Free Adhesive**                      Product Type: Cyanoacrylate Ester  
Date revised: 10/06/06                                      Emergency Number: 800-535-5053

Company:            Novalash, Inc.  
Address:            6116 Skyline Dr. Suite 201, Houston, Texas 77057  
Contact Info:      Office: 1-866-430-1261 Fax: 713-621-5080  
Hours:              Monday – Friday 9a – 6p CST

Web Address: [www.NOVALASH.com](http://www.NOVALASH.com)

## 2- Composition/Information on Ingredients:

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>%</u>	<u>Exposure Limits</u>
Cyanoacrylate Ester	Proprietary	95-100	TWA 0.2 ppm
Urethane Rubber	Trade Secret	5-10	

## 3- Hazards Identification:

Toxicity:                      Skin contact may cause burns. Bonds rapidly and strongly to skin.  
Skin and eye irritant. Estimated oral LD50 more than 5000mg/kg.

Primary routes of Entry:      Inhalation

Signs of exposure:            Vapor is irritating to eyes and mucous membranes above TLV. Prolonged  
and / or repeated overexposure to vapors may produce symptoms of non-  
allergic asthma in sensitive individuals.

## 4- First Aid Measures:

Ingestion:                      Ingestion is unlikely. See supplemental section for emergency action.  
Inhalation:                      Remove to fresh air. If symptoms persist, obtain medical attention.  
Skin contact:                    Soak in warm water. See supplemental section for emergency action.  
Eye contact:                      Flush with warm water. See supplemental section for emergency action.

## 5- Fire Fighting Measures:

Flash Point:                      80°C (176°F) to 93.4°C (200°F) Tag Closed Cup  
Extinguishing Media:            Foam, Dry Chemical or Carbon Dioxide  
Unusual Fire or Explosion Hazards:      Vapors exceeding the flash point will ignite when exposed to flame.  
Special Fire Fighting Procedures:      Wear self-contained breathing apparatus.

## **6-Accidental Release Measures**

Steps to be taken in case of spill or leak: Flood with water to polymerize. Soak up with inert absorbent.

## **7- Handling and Storage:**

Safe storage: Store away from heat and direct sunlight to maximize shelf life. Store inside in a dry location.  
Handling: Keep container tightly closed. Avoid contact with skin. Avoid breathing vapors.

## **8- Protective Equipment:**

Ventilation: Local exhaust ventilation is recommended to maintain vapor level below TLV.  
Respiratory protection: Not applicable with good local exhaust.  
Skin: Polyethylene or non-reactive gloves. Do not use cotton or wool. See supplemental page for more information.  
Eye protection: Safety glasses or goggles with side shields.

## **9- Physical and Chemical Properties:**

Appearance: Black liquid  
Odor: Mild, negligible  
Boiling Point: Greater than 300°F  
Vapor Pressure: Less than 0.2mmHg @25°C  
Vapor Density: Approximately 3 (Air =1)  
Evaporation rate: Not applicable  
Specific Gravity: 1.05  
Solubility in water: Negligible. Polymerized by water.  
VOC Content: Less than 20 g/L (California SCAQMD method 316B)

## **10- Stability and Reactivity**

Stability: Stable  
Hazardous Polymerization: Will not occur  
Incompatibility: Polymerized by contact with water, alcohols, amines, and alkalis.

## **11- Toxicological Information**

See Section 3

## **12-Ecological Information**

No Data

## **13- Disposal Considerations:**

Spill or accidental release: Flood with water to cure (harden) adhesive. Soak up with an inert absorbent.  
Disposal procedures: Incinerate or dispose of in an approved landfill in accordance with local and EPA regulations. Not a RCRA hazardous waste.

## **14- Transportation Information:**

### **Domestic Ground Transport:**

Proper shipping name: Combustible liquid, n.o.s. (more than 450 liters)  
Hazard class or division: Combustible liquid (more than 450 liters)  
Identification number: NA 1993 (More than 450 liters)  
*Exceptions:* Unrestricted under 450 liters  
Marine pollutant: No

### **International Air Transportation (ICAO/IATA):**

Proper shipping name: Aviation regulation liquids, n.o.s. (Cyanoacrylate ester)  
Hazard class or division: 9  
Identification number: UN 3334  
Packing Group: None  
*Exceptions:* Unrestricted under 500 ml

### **Water transportation (IMO/IMDG):**

Proper shipping name: Unrestricted  
Hazard Class or Division: None  
Identification number: None  
Packing Group: None  
Marine pollutant: None

## **15- Regulatory Information**

TSCA 8b Inventory status: All components are listed or exempt  
CERCLA/SARA Section 302 EHS: None  
CERCLA/SARA Section 311/312: Immediate health hazard, Delayed health hazard, Fire, Reactive  
CERCLA SARA 313: None  
California Proposition 65: None  
Canada DSL/NDSL: All components are listed or exempt  
WHMIS hazard class: B.3, D.2.B

## **16- Other Information**

<u>Hazard</u>	<u>NFPA Hazard Code®</u>	<u>HMIS Hazard Code®</u>
Health	2	2
Fire	2	2
Reactivity	1	1
Specific Hazard	No water	Personal protection: See Section 8

NFPA is a registered trademark of the National Fire Protection Association  
HMIS is a registered trademark of the National Paint and Coatings Association

## **First Aid Supplement**

Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue and skin in seconds. Experience has shown that accidents due to Cyanoacrylates are best handled by passive, non-surgical first aid. Treatment of specific types of accidents are suggested as follows:

**Skin Contact-** Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Dried adhesive does not present a health hazard even when bonded to the skin. Avoid contact with clothes, fabric, rags or tissue. Contact with these materials may cause polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear rubber or polyethylene gloves and an apron when handling large amounts of adhesive.

**Skin Adhesion-** First immerse the bonded surfaces in warm, soapy water. Peel off or roll the surfaces open with the end of a blunt edge, such as a spatula or a spoon handle, then remove adhesive from the skin with soap and water. Do not try to pull the surfaces apart with a direct opposing action.

**Eyelid Adhesion-** In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in one to two days. There will be no residual damage. Do not try to open the eyes by manipulation.

**Adhesive in eye-** Adhesive introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, usually in several hours. This will cause periods of weeping until clearance is achieved. It is important to understand that disassociation will normally occur within a matter of hours, even with gross contamination.

**Mouth-** If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow Cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one to two days.

**Burns-** Cyanoacrylates give off heat on solidification. In rare cases, large drops will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of Cyanoacrylate is released from the tissue as described above.

**Surgery-** It should never be necessary to use such drastic action to separate accidentally bonded skin.

Company: Novalash, Inc.  
Revision Date: 10/06/06